


RECEIVED  
CENTRAL FAX CENTER  
OCT 07 2003  
4645.0558

OFFICIAL

- 2 -

In the Claims:


- 
1. (Currently Amended) A common carrier, comprising:
    - a) an elongate support member having a plurality of locating holes disposed thereon; and
    - b) a plurality of current collectors connected to the support member, wherein each of the current collectors comprises planar first and second major faces, the entire extent of which are oriented generally parallel to each other and extending to an intermediate peripheral edge not connected to the peripheral edge of an immediately adjacent current collector and wherein the planar first and second major faces are contactable with an active material to provide an electrode for an electrochemical cell or capacitor.
  2. (Previously Presented) The common carrier of Claim 1, wherein the current collectors are connected to the support member through an external tab extending from the current collectors.
  3. (Previously Presented) The common carrier of Claim 1, wherein the current collectors are spaced apart equidistant from one another and are oriented in substantially the same position relative to the support member.

- 3 -

04645.0558

4. (Previously Presented) The common carrier of Claim 1, further comprising: a secondary material disposed on the first and second major faces of the current collectors.

5. (Currently Amended) A common carrier, comprising:

- 
- a) an elongate, planar support member disposed in a generally horizontal orientation and having at least one datum;
  - b) a plurality of current collectors connected to the support member, wherein each of the current collectors comprises planar first and second major faces, the entire extent of which are oriented generally parallel to each other and extending to an intermediate peripheral edge not connected to the peripheral edge of an immediately adjacent current collector and wherein the planar first and second major faces are contactable with an active material to provide an electrode for an electrochemical cell or capacitor; and
  - c) wherein the support member is capable of being oriented with respect to a tool registrable with the datum.

6. (Previously Presented) The common carrier of Claim 5, wherein the current collectors connect to the support member through an external tab.

- 4 -

04645.0558

7. (Original) The common carrier of Claim 6, wherein the external tab connects at a substantially perpendicular orientation with the support member.
8. (Previously Presented) The common carrier of Claim 6, further comprising: a secondary material disposed on the first and second major faces of the current collectors.
9. (Cancelled)
10. (Original) The common carrier of claim 4 wherein the secondary material is of carbon or gold.
11. (Currently Amended) A common carrier, comprising:
- a) an elongate support member having a plurality of locating holes disposed thereon; and
  - b) a plurality of current collectors, each connected to the support member by a tab, wherein each of the current collectors comprises planar first and second major faces, the entire extent of which are oriented generally parallel to each other and extending to an intermediate peripheral edge not connected to the peripheral edge of an immediately adjacent current collector and wherein the planar first and second major faces are contactable with an active material to provide an electrode for an electrochemical cell or capacitor; and
  - c) a secondary material contacted to the first and

- 5 -

04645.0558



second major faces of the current collectors.

12. (Original) The common carrier of claim 11 wherein the secondary material is of carbon or gold.
-